


SAE MALE 45° FLARE


MASCHIO SAE SV.45°



part nr. codice	hose ID			thread T	d		E		cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]
0402580513	5/16"	8,0	05	5/8-18	0,22	5,5	0,67	17	1,14	29
0402580613	3/8"	9,5	06	5/8-18	0,28	7,0	0,67	17	1,14	29
0402581227	3/4"	19,0	12	1.1/16-12	0,59	15,0	1,06	27	1,54	39

SAE FEMALE 45° FLARE


FEMMINA SAE SV. 45°



art nr. codice	hose ID			thread T	d		E		cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]
0416290513	5/16"	8,0	05	5/8-18	0,22	5,5	0,87	22	0,59	15,0
0416290613	3/8"	9,5	06	5/8-18	0,28	7,0	0,87	22	0,59	15,0
0416291227	3/4"	19,0	12	1.1/16-20	0,59	15,0	1,26	32	0,75	19,0

SAE FEMALE 90° FLARE 45° ELBOW


FEMMINA SAE 90° SV. 45°



part nr. codice	hose ID			thread T	d		E		cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
0427290513	5/16"	8,0	05	5/8-18	0,22	5,5	0,87	22	1,14	29	1,22	31
0427290613	3/8"	9,5	06	5/8-18	0,28	7,0	0,87	22	1,30	33	1,26	32

SAE FEMALE 45° FLARE 45° ELBOW

FEMMINA SAE 45° SV. 45°



part nr. codice	hose ID			thread T	d		E		cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
0428290513	5/16"	8,0	05	5/8-18	0,22	5,5	0,87	22	2,56	65,0	0,67	17,0
0428290613	3/8"	9,5	06	5/8-18	0,28	7,0	0,87	22	1,65	42,0	0,67	17,0
0428290613L	3/8"	9,5	06	5/8-18	0,28	7,0	0,87	22	1,97	50,0	0,71	18,0

