



2SC K - PROWASH

Inner Tube : synthetic rubber
 Reinforcement : 2 high tensile steel braid
 Cover : oil, abrasion, ozono and weather resistant synthetic rubber
 Working Temperature : -40°C / +155°C

2SC K - PROWASH

Sottostrato : gomma sintetica
 Rinforzo : 2 trecce in acciaio ad alto carico
 Copertura : gomma sintetica resistente agli olii, ozono e agenti atmosferici
 Temperatura di Esercizio : -40°C / +155°C

PROwash 2SC K

part nr. codice	ID			OD		WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
black / nero													
0121401905	5/16"	8,0	05	0,59	15,1	5801	400	23205	1600	4,53	115,0	0,233	0,348
0121401906	3/8"	9,5	06	0,69	17,5	5801	400	23205	1600	5,12	130,0	0,292	0,435
0121401908	1/2"	12,7	08	0,83	21,0	3988	275	15954	1100	7,09	180,0	0,375	0,559
blue / blu													
0121401704	1/4"	6,4	04	0,54	13,7	5801	400	23205	1600	3,94	100,0	0,203	0,302
0121401705	5/16"	8,0	05	0,59	15,1	5801	400	23205	1600	4,53	115,0	0,233	0,348
0121401706	3/8"	9,5	06	0,69	17,5	5801	400	23205	1600	5,12	130,0	0,292	0,435
0121401708	1/2"	12,7	08	0,83	21,0	3988	275	15954	1100	7,09	180,0	0,375	0,559
grey / grigio													
0121402104	1/4"	6,4	06	0,54	13,7	5801	400	23205	1600	3,94	100,0	0,203	0,302
0121402105	5/16"	7,9	08	0,59	15,1	5801	400	23205	1600	4,53	115,0	0,233	0,348
0121402106	3/8"	9,5	10	0,69	17,5	5801	400	23205	1600	5,12	130,0	0,292	0,435
0121402108	1/2"	12,7	12	0,83	21,0	3988	275	15954	1100	7,09	180,0	0,375	0,559

On request other colour available / Su richiesta disponibili alter colorazioni.