



MTKH THERMOPLASTIC HOSE

Inner Tube : thermoplastic polyester
 Reinforcement : 1 aramidic fiber braid + 1 high tensile steel braid
 Cover : polyurethane, on request it is also available micro perforated
 Working Temperature : -40°C / +100°C
 Applications : for oleodynamic use

MTKH TUBO TERMOPLASTICO

Sottostrato : poliestere termoplastico
 Rinforzo : 1 treccia in fibra aramidica + 1treccia in acciaio ad alto carico
 Copertura : poliuretano, a richiesta microperforato
 Temperatura di Esercizio : -40°C / +100°C
 Applicazioni : per utilizzo oleodinamico

PRO MTKH

part nr. codice	ID			OD		WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
0132412304	1/4"	6,4	04	0,57	14,5	10152	700	40609	2800	1,58	40,0	0,174	0,260
0132412306	3/8"	9,5	06	0,71	18,0	6164	425	24656	1700	2,36	60,0	0,231	0,344
0132412308	1/2"	13,0	08	0,87	22,0	5439	375	21755	1500	2,96	75,0	0,335	0,500
0132412312	3/4"	19,2	12	1,11	28,2	3263	225	13053	900	5,91	150,0	0,442	0,659



MTK THERMOPLASTIC HOSE

Inner Tube : polyamide
 Reinforcement : 1 aramidic fiber braid + 1 high tensile steel braid
 Cover : polyurethane, on request it is also available micro perforated
 Working Temperature : -40°C / +100°C

MTK TUBO TERMOPLASTICO

Sottostrato : poliammide
 Rinforzo : 1 treccia in fibra aramidica + 1treccia in acciaio ad alto carico
 Copertura : poliuretano, a richiesta microperforato
 Temperatura di Esercizio : -40°C / +100°C

PRO MTK

part nr. codice	ID			OD		WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
0132412303	3/16"	4,8	03	0,45	11,3	7252	500	29007	2000	1,18	30,0	0,112	0,167
0132412404	1/4"	6,4	04	0,57	14,5	10152	700	40609	2800	1,58	40,0	0,168	0,251
0132412405	5/16"	8,0	05	0,63	16,0	7252	500	29007	2000	1,97	50,0	0,188	0,280
0132412406	3/8"	9,5	06	0,71	18,0	6164	425	24656	1700	2,36	60,0	0,224	0,334
0132412408	1/2"	13,0	08	0,87	22,0	5439	375	21755	1500	2,96	75,0	0,322	0,480
0132412410	5/8"	16,0	10	0,99	25,0	3626	250	14503	1000	4,33	110,0	0,371	0,553
0132412412	3/4"	19,2	12	1,11	28,2	3263	225	13053	900	5,91	150,0	0,432	0,644
0132412416	1"	25,8	16	1,39	35,4	2901	200	11603	800	9,85	250,0	0,543	0,810

Special / Speciale: MTKM

0132412506	3/8"	9,5	06	0,74	18,8	10152	700	40609	2800	3,55	90,0	0,250	0,373
------------	------	-----	----	------	------	-------	-----	-------	------	------	------	-------	-------



JET CLEANING SEWER HOSE

Inner Tube : thermoplastic polyester
 Reinforcement : 2 polyester fiber braids
 Cover : polyurethane
 Working Temperature : -40°C / +100°C

TUBO PULIZIA AD ALTA PRESSIONE

Sottostrato : poliestere termoplastico
 Rinforzo : 2 treccie in fibra poliestere
 Copertura : poliuretano
 Temperatura di Esercizio : -40°C / +100°C

PRO CLEAN

Color : ORANGE

Colore : ARANCIONE

part nr. codice	ID			OD		WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
0132133008	1/2"	13,0	08	0,88	22,4	4061	280	10152	700	2,96	75,0	0,198	0,295
0132133012	3/4"	19,2	12	1,16	29,5	2901	200	7252	500	4,73	120,0	0,305	0,454
0132133016	1"	25,6	16	1,45	36,8	2901	200	7252	500	5,91	150,0	0,426	0,635
0132133020	1.1/4"	32,0	20	1,79	45,5	2901	200	7252	500	9,26	235,0	0,614	0,915